

1. An integrated circuit assembly comprising:

a semiconductive substrate comprising a plurality of field effect transistors having electrically coupled sources and electrically coupled drains comprising regions of the substrate adjacent to a surface of the substrate, and wherein the electrically coupled sources and the electrically coupled drains are collectively configured to conduct power currents in excess of one Ampere; and

a package having a plurality of source contacts and a plurality of drain contacts configured to couple with the electrically coupled sources and the electrically coupled drains of the semiconductive substrate, and wherein the source contacts and the drain contacts are provided adjacent to the surface of the package.

2. The assembly of claim 1 wherein the semiconductive substrate further comprises a plurality of source contacts and a plurality of drain contacts coupled with respective ones of the sources and the drains of the field effect transistors, and wherein the source contacts and the drain contacts of the package are configured to couple with respective ones of the source contacts and the drain contracts of the power semiconductor switching device.

3. The assembly of claim 1 further comprising at least one metallization layer coupled with the substrate and configured to couple at least some of the sources in parallel and at least some of the drains in parallel.

4. The assembly of claim 3 wherein the semiconductive substrate further comprises a horizontal interconnect layer formed upon and coupled with the at least one metallization layer, and the horizontal interconnect layer defines a plurality of source contacts and a plurality of drain contacts configured to couple with respective ones of the source contacts and the drain contacts of the package.

5. The assembly of claim 4 wherein the package comprises at least one horizontal interconnect layer to provide the source contacts and the drain contacts.

6. The assembly of claim 1 wherein all electrical connections intermediate the sources and the drains of the substrate and the source contacts and the drain contacts of the package pass through the surface of the substrate.

7. The assembly of claim 1 wherein the package includes one terminal source contact and one terminal drain contact electrically coupled with respective ones of the source contacts and the drain contacts of the package and adapted to electrically couple with devices external of the semiconductor switching device.

8. The assembly of claim 7 wherein the package provides a plurality of electrical paths intermediate the one terminal source contact and the one terminal drain contact and respective ones of the source contacts and the drain contacts of the package, and the electrical paths individually have a resistance less than 1 milliOhm.

9. The assembly of claim 1 wherein the semiconductive substrate comprises a flip chip semiconductive die.

10. The assembly of claim 1 wherein the source contacts and the drain contacts of the power semiconductor device are arranged in alternating columns, and wherein the package comprises a vertical laminate package comprising a plurality of conductive layers corresponding to respective ones of the columns.

11. The assembly of claim 1 wherein the package comprises at least one horizontal interconnect layer.

12. The assembly of claim 11 wherein the at least one horizontal interconnect layer is spaced from the power semiconductor device; and further comprising a plurality of electrical interconnects intermediate the horizontal interconnect layer and the source contacts and the drain contacts of the power semiconductor device.

13. The assembly of claim 1 wherein the number of source contacts of the power semiconductor device is less than the number of sources and the number of drain contacts of the power semiconductor device is less than the number of drains.

14. The assembly of claim 1 wherein the semiconductive substrate comprises a monolithic substrate including the field effect transistors and auxiliary circuitry.

15. The assembly of claim 1 wherein the semiconductive substrate comprises a monolithic substrate including the field effect transistors and auxiliary circuitry coupled with the plurality of field effect transistors.

16. The assembly of claim 1 wherein the field effect transistors comprise MOSFET devices.

17. An integrated circuit assembly comprising:
a power semiconductor switching device comprising:
a semiconductive substrate having a surface; and
a power transistor formed using the substrate and having a plurality of source contacts and drain contacts adjacent to the surface and configured to conduct power currents; and

a package having a plurality of source contacts and a plurality of drain contacts corresponding to and electrically coupled with respective ones of the source contacts and the drain contacts of the power semiconductor device.

18. The assembly of claim 17 wherein the power transistor comprises a plurality of planar field effect transistors.

19. The assembly of claim 17 wherein the power transistor comprises a plurality of planar field effect transistors coupled in parallel.

20. The assembly of claim 17 further comprising at least one metallization layer coupled with the substrate and configured to couple at least some of the source contacts in parallel and at least some of the drain contacts in parallel.

21. The assembly of claim 20 further comprising a horizontal interconnect layer formed upon and coupled with the at least one metallization layer, and the horizontal interconnect layer defines the source contacts and the drain contacts of the power transistor.

22. The assembly of claim 17 wherein the package comprises at least one horizontal interconnect layer to provide the source contacts and the drain contacts of the package.

23. The assembly of claim 17 wherein all electrical connections intermediate the source contacts and the drain contacts of the substrate and the source contacts and the drain contacts of the package pass through the surface of the substrate.

24. The assembly of claim 17 wherein the power transistor is configured to conduct power currents in excess of one Ampere.

25. The assembly of claim 17 wherein the package includes one terminal source contact and one terminal drain contact electrically coupled with respective ones of the source contacts and the drain contacts of the package and adapted to electrically couple with devices external of the semiconductor switching device.

26. The assembly of claim 25 wherein the package provides a plurality of electrical paths intermediate the one terminal source contact and the one terminal drain contact and respective ones of the source contacts and the drain contacts of the package, and the electrical paths individually have a resistance less than 1 milliOhm.

27. The assembly of claim 17 wherein the semiconductive substrate comprises a flip chip semiconductive die.

SUB
27
28
29
30
31
28. The assembly of claim 17 wherein the source contacts and the drain contacts of the power semiconductor device are arranged in alternating columns, and wherein the package comprises a vertical laminate package comprising a plurality of conductive layers corresponding to respective ones of the columns.

29. The assembly of claim 17 wherein the package comprises at least one horizontal interconnect layer.

30. The assembly of claim 29 wherein the at least one horizontal interconnect layer is spaced from the power semiconductor device; and further comprising a plurality of electrical interconnects intermediate the horizontal interconnect layer and the source contacts and the drain contacts of the power semiconductor device.

31. The assembly of claim 17 wherein the number of source contacts of the power semiconductor device is less than the number of sources and the number of drain contacts of the power semiconductor device is less than the number of drains.

32. The assembly of claim 17 wherein the semiconductive substrate comprises a monolithic substrate including the field effect transistors and auxiliary circuitry.

33. The assembly of claim 17 wherein the semiconductive substrate comprises a monolithic substrate including the field effect transistors and auxiliary circuitry coupled with the plurality of field effect transistors.

34. The assembly of claim 17 wherein the power transistor comprises a plurality of MOSFET devices.

Please cancel claims 35-66.